



Retail Jewelry POP Display


501412

Assembly Instructions

Before beginning, please read through all the assembly instructions carefully.

PARTS LISTS

| | | |
|--------|-----------------------------|----|
| 954104 | Back Graphic Panel | 1 |
| 921348 | Support Angle | 2 |
| 954101 | LH Side Graphic Panel | 1 |
| 954102 | RH Side Graphic Panel | 1 |
| 700530 | Large Shelf | 3 |
| 700529 | Small Shelf | 1 |
| 954103 | Header Graphic Panel | 1 |
| 940016 | 10-24 x 3/4" Machine Screw | 16 |
| 940313 | 10-24 Hex Nut | 16 |
| 940239 | 1/4-20 x 3/4" Machine Screw | 24 |



Step 1: Secure each support angle to the back graphic panel using (4) 10-24 x 3/4" machine screws and (4) 10-24 hex nuts for each support angle.

Step 1



If you have any questions, please call:
Black River Display Group (419) 524.2000



Step 2

Step 2 Attach LH side graphic panel and RH side graphic panel to the back panel assembly using (3) 10-24 x 3/4" machine screws and (3) 10-24 hex nuts for each side panel.



Step 3 Slide (1) large shelf along the floor into the base area as shown in photo. Be sure the two pre-installed insert nuts are to the back.



Step 3

Step 4 Secure the base shelf in place with (6) 1/4-20 x 3/4" screws. Two through the LH side graphics panel, two through the back graphic panel and two through the RH side graphic panel. **Do not completely tighten at this time**



Step 4

Step 5 Lay the display structure on its back.



Step 6 Drop in the second large shelf and secure in place with (4) 1/4-20 x 3/4" machine screws, two through the LH side graphic panel and two through the RH side graphic panel. **Again, do not completely tighten at this time.**



Step 6

If you have any questions, please call:
Black River Display Group (419) 524.2000

Step 7 Repeat step 6 with the last large shelf and one small shelf.



Step 7

Step 8 Stand the display back upright



Step 8

Step 9 Put the remaining (6) 1/4-20 x 3/4" machine screws through the back graphic panel into the pre-installed insert nuts in the shelves.
At this time, tighten ALL the machine screws



Step 9

Step 10 Position the header graphic panel on the inside of the back panel and secure with (2) 10-24 x 3/4" machine screws and (2) 10-24 hex nuts and tighten.



Step 10

If you have any questions, please call:
Black River Display Group (419) 524.2000